

Marcatempo

Marcatempo con badge aziendali per caricare automaticamente le timbrature nella piattaforma HR Compendium Platform.



Ecco le nostre soluzioni



MiniClock-4
BIO

MiniClock-4
RFID

Thanks to a wide range of communication modes meet all needs.

Terminal interface is based on exchange of files and commands.

The operating system provides great performance. It has weather resistant case, reliability and low cost.

MiniClock-4

Web services HTTP/HTTPS client. Easy way to control terminal using on-line mode with HTTP server.

- HTTP server terminal configuration using standard browser.
- Client Web browser take and display on-line information from HTTP/HTTPS server.
- Client SQL and MySQL send transit logs directly to network DB.
- Client SMTP able to send mails.
- FTP client upload file to a FTP server according build-in scheduler.
- FTP Server terminal control by a FTP client.
- USB 2.0, Ethernet 10-100 Mbps, WiFi, UMTS modem and RS232, RS485.
- Badge supported: RFID 125 KHz and Mifare 14443-A, 14443-B, biometric technology.

Specifiche tecniche

LCD 240 x 320 TFT 65536 colors Display with white led back-light
RGB multi-color semaphore
Monotone buzzer
Build-in RFID 125 KHz or 13.56 Mhz reader Mifare/NFC
Build-in biometric optical reader
DDR3 512 Mbyte memory
1 Ghz Cortex A8 CPU
High precision temperature-compensated real time clock
10-100 Auto-MDIX Ethernet
2 x USB 2.0 port
Serial communication ports RS485
2 internal relays
2 digital inputs
PoE Power supply or 9-36 Vdc with ext, adapter
Size W H D 72 x 178 x 45

FingerClock 4P RFID Mifare



Specifiche tecniche

LCD VGA 480 x 800 TFT 65536 colors Display with white led back-light

Touch-screen

Polyphonic stereo audio

Build-in 2 x RFID 125 KHz and 2 x 13.56 Mhz reader Mifare/NFC

DDR3 32bits 1GbyteFC04-RFIDFC04 Rfdi White RAL7035

800MHz 2 x CortexA8 CPU

High precision temperature-compensated real time clock

Linux operating system

10-100 Auto-MDIX Ethernet

2 x USB 2.0 port

Three serial communication ports RS232/485

Two internal relays

2 digital inputs

Internal UMTS dongle

Internal WiFi dongle

External USB plug for pen-drive

PoE Power supply or 9-36 Vdc with ext, adapter

Size W H D 165 x 158 x 60